

SPRING SPECIALS



7018

AWS A5.1 E7018 H4



- All-Position, Multiple-Pass
- Excellent charpy impact values at sub-zero temperatures (65 ft-lbs at -20°)
- For structural and fabrication steels such as beams, angles, channels and plates, cast steels, process piping steels, cold rolled steel, and shipbuilding steels

Part Number	10 lb box
WE7018093	E7018 3/32"
WE7018125	E7018 1/8"
WE7018156	E7018 5/32"
WE7018187	E7018 3/16"

Also available in 5 lb box
Call for Volume Pricing

7018R

AWS A5.1 E7018 H4R



- Premium moisture resistant coating
- Excellent restrike without porosity
- Reduced moisture pickup vs. Inweld 7018

Part Number	10 lb box
WE7018R093	E7018R 3/32"
WE7018R125	E7018R 1/8"
WE7018R156	E7018R 5/32"
WE7018R187	E7018R 3/16"

Also available in 5 lb box
Call for Volume Pricing

7014

AWS A5.1 E7014



- Easy to use, high speed electrode for welding carbon and low alloy steels
- used for tack welding sheet metal or galvanized, rusty or dirty plate steels, ornamental iron, mobile home frames, automobiles and railcars, storage tanks, machine parts, structural steel for buildings

Part Number	10 lb box
WE7014093	E7014 3/32"
WE7014125	E7014 1/8"
WE7014156	E7014 5/32"
WE7014187	E7014 3/16"

Also available in 5 lb box
Call for Volume Pricing

7024

AWS A5.1 E7024



- Single pass welding on horizontal or flat fillet welds
- Used on heavy construction and earth moving equipment, truck bodies, ships barges, and railcars, as well as many other mild steel and alloy steel applications.

Part Number	10 lb box
WE7024093	E7024 3/32"
WE7024125	E7024 1/8"
WE7024156	E7024 5/32"
WE7024187	E7024 3/16"

Also available in 5 lb box
Call for Volume Pricing

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
3962 Portland Street
Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
© Inweld Corporation

Texas
9300 Lawndale St.
Houston, TX 77012

Mild Steel Electrodes Vacuum Sealed



6010

AWS A5.1 E6010



- All-Position, Multiple-Pass
- For pressure pipes, pressure vessels, oil marine platforms, storage tanks, ship hulls, buildings, and galvanized steel storage tanks

Part Number	10 lb box
WE6010093	E6010 3/32"
WE6010125	E6010 1/8"
WE6010156	E6010 5/32"
WE6010187	E6010 3/16"

Also available in 5 lb box
Call for Volume Pricing

6013

AWS A5.1 E6013



- All-Position
- Designed for thin sheet metal or light gauge steel but with sufficient penetration for welding medium gauge steels

Part Number	10 lb box
WE6013125	E6013 1/8"
WE6013156	E6013 5/32"
WE6013187	E6013 3/16"

Also available in 5 lb box
Call for Volume Pricing

6022

AWS A5.1 E6022



- For burn-through spot welding of roof decking to support beams
- Fast down-hand, single pass welding of light gauge materials such as sheet metal
- Excellent strike and restrike action

Part Number	10 lb box
WE6022125	E6022 1/8"
WE6022156	E6022 5/32"

Also available in 5 lb box
Call for Volume Pricing

309L

AWS A5.4 E309L-16



- For welding 309, 309L as well as other 300 series
- Excellent for joining stainless steel to mild or carbon steels, buttered passes on steel overlay work and for welding AISI 304 clad stainless

Part Number	10 lb box
WE309L16093	E309L-16 3/32"
WE309L16125	E309L-16 1/8"
WE309L16156	E309L-16 5/32"
WE309L16187	E309L-16 3/16"

Call for Volume Pricing

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
3962 Portland Street
Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
© Inweld Corporation

Texas
9300 Lawndale St.
Houston, TX 77012

Rod Ovens

- 150C max temp
- Analog thermostat



Part Number

AUEQ10SET	10 lb
AUEQ20S	20 lb
AUEQ50SW	50 lb
AUEQ100DT3	100 lb

Inweld[®]
Welding Alloys & Supplies

Pipe Stand S-Type Standard-J

- V-head
- T-handle for extra safety in securing V-head
- Heavy duty legs
- Wider tripod leg gap for extra stability
- 23.59 lbs (10.7 kg)
- Box size: 7.75" x 8.75" x 34.5" (197 x 222 x 876 mm)
- Similar to BB3900
- Load capacity: 2500 lbs (1135 kg)



Part Number
PJ2947FLD

Welding Table with Casters

- Galvanized 14Ga Steel Sheet Table Top
- 36" x 20"
- Slag Tray
- 220 lb Capacity
- Assembly Required
- Box Dimensions: 37" x 21" x 5"



Part Number
MIWT362036NT2

Portable Welding Table

- Galvanized 14Ga Steel Sheet Table Top
- 40" x 24"
- Folding Legs
- 400 lb Capacity
- Limited Assembly Required
- Box Dimensions: 46" x 27" x 5"



Part Number
MIWT402436V2

While Supplies Last

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
3962 Portland Street
Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
© Inweld Corporation

Texas
9300 Lawndale St.
Houston, TX 77012

70S-6

AWS A5.18 70S6

- Engineered for automotive welding applications
- Very stable arc at high wire feed speeds
- Premier choice for spray transfer applications



Part Number	
0270S6023	0.023 x 2lb Spool
0270S6030	0.030 x 2lb Spool
0270S6035	0.035 x 2lb Spool
1170S6023	0.023 x 11lb Spool
1170S6030	0.030 x 11lb Spool
1170S6035	0.035 x 11lb Spool
3370S6035LW	0.035 x 33lb Spool
3370S6045LW	0.045 x 33lb Spool
4470S6035	0.035 x 44lb Spool
4470S6045	0.045 x 44lb Spool
50070S6035	0.035 x 550lb Drum
50070S6045	0.045 x 550lb Drum

Call for Volume Pricing

Inweld 71T-GS Mild Steel Flux-Cored MIG Wire

AWS A5.20 71TGS

- Works well on small 110 volt power source/feeders
- Single pass welding of thin-gauge carbon steel, ranging from 3/16 Inch to 22 gauge
- Requires no external gas-shielding
- For lap and butt welds on galvanized sheet metal, repair of automobile sheet metal, welding ductwork and joining of galvanized sheet metal



Part Number	
0271TGS030	0.030 x 2 lb Spool
0271TGS035	0.035 x 2 lb Spool
1071TGS030	0.030 x 10 lb Spool
1071TGS035	0.035 x 10 lb Spool

Inweld
Welding Alloys & Supplies



Masterweld M25 MIG Gun

- Spring support to reduce wear and tear
- Internal fittings insulated with high temperature glass stranded insulation
- Improved tolerances to ensure tighter fit on locking mechanism on handle
- Made in USA for the past 15 years
- Replacement triggers available



Part Number	
169-594	10' M25 0.030" - 0.035"
169-596	12' M25 0.030" - 0.035"
169-598	15' M25 0.030" - 0.035"
169-599	15' M25 0.035" - 0.045"
169-597	20' M25 0.030" - 0.035"
169-600	25' M25 0.030" - 0.035"

Anti-Spatter Plant Based

FEATURES AND BENEFITS

- Ready to use aerosol
- Dries instantly
- Non-toxic & biodegradable
- No chlorinated solvents
- Odorless
- Silicone free for easy painting

APPLICATION

- Prevents spatter build up on MIG nozzles, tips, fixtures and metals during welding



Part Number
ANTISPATPB

71T-1 Flux-Cored Carbon Steel Wire

AWS A5.20 71T1MC



- For welding mild and medium carbon steels in all positions.
- Lower spatter and fume emissions than conventional products in this class
- Used where a minimum tensile strength of 70,000 psi is required in the deposited weld metal
- Provides optimum welding performance in argon/ carbon dioxide shielding gas but is also formulated to perform very well with 100% CO2

Part Number

71T-1

1071T1035	0.035" x 10lb
1071T1045	0.045" x 10lb
3371T1035	0.035" x 33 lb
3371T1045	0.045" x 33 lb
4471T1062	1/16" x 44lb
50071T1045	0.045" x 440lb

71T1-9 (Seismic Rated)

3371T1-9C/9M045	0.045" x 33lb
-----------------	---------------

Call for Volume Pricing

F Clamps

- Profiled rail and spatter resistant spindle
- High quality heat-treated steel and plated for strength and durability
- Arm made from tempered, drop-forged steel
- Reversible arm converts the holding clamp to a spreader bar
- Replaceable swivel



Part Number

1200 PSI	
HT1212	12"
HT1224	24"
HT1232	32"

C Clamp Pliers



Part Number

HTLP06	6"
HTLP09	9"
HTLPSP06	6" w/ swivel pads
HTLPSP09	9" w/ swivel pads

Open End Erector Wrenches



Part #		Qty on hand
N10E3210	1/2" bolt, 7/8" HD Nut KT3210	158
N10E3211	5/8" bolt, 1-1/16" HD Nut 3211	217
N10E3222	3/4" bolt, 1-1/8" HD Nut 3222	173
N10E3212	3/4" bolt, 1-1/4" HD Nut 3212	8
N10E3213	7/8" bolt, 1-7/16" HD Nut 3213	222
N10E3214	1" bolt, 1-5/8" HD Nut 3214	206

WHILE SUPPLIES LAST

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
3962 Portland Street
Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
© Inweld Corporation

Texas
9300 Lawndale St.
Houston, TX 77012

Miller® Style Foot Pedal



- Used on: - Miller Tig welders like the Econotig
 - Syncrowave 180, 200, and 250
 - Dynasty 200dx
 - Any Miller solid state power source with serial number JK 674521 and higher using a 14 pin connector
 - T200 Norstar welder
- Includes 25 ft (8 m) cord
- Replacement for the Miller RFCS-14 (Miller P/N 043 554) and the Miller RFCS-14HD (Miller P/N 194 744)



Part Number	Stock on Hand
AUFOOTPEDAL	142

150 Amp Miller® Style MIG Gun

Miller® Style Spool Gun

- 10' Lead
- Air Cooled
- 150 amps
- Uses standard Miller style consumables

- 10' lead
- Air Cooled
- 22.5 volts, 135 amps, 30% duty cycle using Argon shielding gas
- 4" (102 mm) max. spool size

Part Number

AUM10GUN

Stock on Hand

274



Part Number

AUSPLGUN-M

Stock on Hand

56



WHILE SUPPLIES LAST

Due to marketplace volatility, prices are subject to change without notice.



INVENTORY REDUCTION



150 Amp Hobart® Style MIG Gun

- 10' Lead
- Air Cooled
- 150 amps
- Uses standard Miller style consumables

Part Number

AUH10GUN

Stock on Hand

50



150 Amp Lincoln® Style MIG Gun

- 10' Lead
- Air Cooled
- 150 amps
- Uses standard Tweco style consumables

Part Number

AUL10GUN

Stock on Hand

214



Spool Guns

- 10' lead
- Air Cooled
- 22.5 volts, 135 amps, 30% duty cycle using Argon shielding gas
- 4" (102 mm) max. spool size

Hobart® Style Spool Gun

Part Number

AUSPLGUN-H

Stock on Hand

92



Lincoln® Style Spool Gun

Part Number

AUSPLGUN-L

Stock on Hand

197



WHILE SUPPLIES LAST

Due to marketplace volatility, prices are subject to change without notice.



HANDHELD MAPP / PROPANE TORCHES

AVAILABLE NOW!

Inweld
Welding Alloys & Supplies

Pencil Flame Micro Torch

- For use with dual gas MAPP or Propane
- Durable brass and stainless steel construction
- For professional and home use
- Portable, efficient and easy to operate
- All-position brazing and soldering
- Fits all standard MAPP and LP tanks

Part Number
MT854



Extended Duty Torch

- Flame tip swivels 360°
- Pressure regulated
- Adjustable flame control
- Rugged brass and stainless steel construction

Part Number
MAP30G



Auto-Ignition Brazing and Soldering Torch

- Flame tip swivels 360°
- Pressure regulated
- Self-lighting piezo ignition
- Brass and stainless steel construction

Part Number
MAP75G



Pencil Flame Heating Torch

- Adjustable knob
- Durable brass and stainless steel construction
- For professional and home use
- Portable, efficient and easy to operate
- Self-lighting piezo ignition
- All-position brazing and soldering
- Fits all standard MAPP and LP tanks

Part Number
HT850B



Due to marketplace volatility, prices are subject to change without notice.

Cutting Attachments



- Part Number
CUTATTACHMD MD Cut Attachment (V-1350)
- CUTATTACHHD** HD Cut Attachment (V-2460)
- CUTHANDHD** HD Cut Handle (Victor Style)
- CUTHANDMDCVFB *** MD Weld Handle (V-100)
- CUTHANDHDCVFB *** HD Weld Handle (V-315)
- CUTTORCH21CVFB *** Cutting Torch Only 21"

* w/ check valve and flashback arrestor



Portable Weld & Cut Kit V Style

Kit Includes:

- Oxygen regulator: V155-OX
- Acetylene regulator: V155-AC
- Torch handle: V100
- Cutting attachment: V1350
- Cutting tip: 0-3-101
- Welding tip: VM-WO
- 12.5' x 3/16" twin hose with "B" fittings • Check valves
- Goggles
- Tip cleaner,
- Spark lighter
- 8 way tank wrench
- Cylinder tote



Part Number
CUTKITPORT
CYLTOTE

TWIN Hose



Part Numbers	Description	Case Qty.
1/4"		
Grade R		
HTD1425BB	Twin Hose Grade R 1/4 x 25' BB Fittings	10
HTD1450BB	Twin Hose Grade R 1/4 x 50' BB Fittings	5
HTD14100BB	Twin Hose Grade R 1/4 x 100' BB Fittings	2
HTD14RE	Twin Hose Grade R 1/4 x 400' Reel	1
Grade T		
HTDT1425BB	Twin Hose Grade T 1/4 x 25' BB Fittings	10
HTDT1450BB	Twin Hose Grade T 1/4 x 50' BB Fittings	5
HTDT14100BB	Twin Hose Grade T 1/4 x 100' BB Fittings	2
HTDT14RE	Twin Hose Grade T 1/4 x 400' Reel	1

Due to marketplace volatility, prices are subject to change without notice.

Medium Duty Regulators



- Designed for medium capacity applications
- Single stage design brass body
- Clamshell Packaging

Part Number

REG350ACET300
REG350ACET510
REG3500XY540



Heavy Duty Regulators

- Designed for high capacity applications
- Single stage design brass body
- Boxed Packaging



Part Number

REG450ACET300
REG450ACET510
REG4500XY540

Nitrogen Regulators



- Single stage design brass body
- Clamshell Packaging

CO2 Regulator with Solenoid and Timer



N3020024



N3020025

Part Number

REGNPURGMD580
REGNPURGHD580



Part Number

Stock on Hand

N3020024
N3020025

122
 33

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
 3962 Portland Street
 Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
 © Inweld Corporation

Texas
 9300 Lawndale St.
 Houston, TX 77012

Pressure Gauges



1.5"

- Single scale
- Brass case
- 1/8" brass inlet

Part Number	Pressure Rating	Qty on hand
PG150030BP	1.5" - 30psi	1565
PG150100BP	1.5" 100psi	1942
PG150200BP	1.5" 200psi	1998
PG150400BP	1.5" 400psi	1573
PG1530CFH	1.5" 30 CFH	435
PG154000BP	1.5" 4,000psi	659
PG15PC *	1.5" Plastic Cover	



2"

- Single scale
- Brass case
- 1/4" brass inlet

Part Number	Pressure Rating	Qty on hand
PG200030CS	2" - 30psi	322
PG200100CS	2" 100psi	348
PG200200CS	2" 200psi	294
PG200400CS	2" 400psi	258
PG204000CS	2" 4,000psi	465



2.5"

- Single scale
- Brass case
- 1/4" brass inlet

Part Number	Pressure Rating	Qty on hand
PG250030CS	2.5" - 30psi	375
PG250100CS	2.5" 100psi	482
PG250200CS	2.5" 200psi	186
PG254000CS	2.5" 4000psi	192
PG25PC *	2.5" Plastic Cover	274



* Call for pricing

Due to marketplace volatility, prices are subject to change without notice.

Air Acetylene Brazing Kit

Kit Includes:

- Torch Handle A
- Regulator CGA B & MC "A"
- Swirl Flame Tips
 - Tip air acetylene qd swirl A5 7/32" ID
 - Tip air acetylene qd swirl A8 1/4" ID
 - Tip air acetylene qd swirl A14 3/8" ID
 - Tip air acetylene qd swirl A32 1/2" ID
- Hose with Fitting "A"

Part Number
CUTKITAA

Part Number
REG250ACET510
AAHANDQD
TIPAIRACETA3
TIPAIRACETA5
TIPAIRACETA8
TIPAIRACETA11
TIPAIRACETA14
TIPAIRACETA32

Acet. Reg. Med Duty 250 CGA 510
Replacement Handle Quick Disconnect B Valve
Tip Air Acet. Quick Disconnect Swirl A3
Tip Air Acet. Quick Disconnect Swirl A5
Tip Air Acet. Quick Disconnect Swirl A8
Tip Air Acet. Quick Disconnect Swirl A11
Tip Air Acet. Quick Disconnect Swirl A14
Tip Air Acet. Quick Disconnect Swirl A32



CYLINDER HOLDER & WALL BRACKETS



Part Number
CYH104 3 1/8" - 4 3/4" (98 - 110 mm), 1.87 lbs (850 gms)
CYH106 6 1/2" - 7 1/4" (165 - 184 mm), 2.535 lbs (1.15 kg)
CYH108 8" - 8 3/4" (203 - 222 mm), 2.865 lbs (1.3 kg)
CYH185 8 1/2" - 9" (215 - 228 mm), 2.975 lbs (1.35 kg)
CYH112 12" - 13" (305 - 330 mm), 3.745 lbs (1.7 kg)
CYH114 14 1/2" - 15 1/4" (368 - 387 mm), 4.3 lbs (1.95 kg)

Balloon Fillers

Part Number
REGBAL580G



Part Number
REGBALDual

Due to marketplace volatility, prices are subject to change without notice.



Pennsylvania
3962 Portland Street
Coplay, PA 18037

inweldcorporation.com
Phone: 800.346.5368
Fax: 877.346.5368
© Inweld Corporation

Texas
9300 Lawndale St.
Houston, TX 77012

Cylinder Carts



Inweld[®]
Welding Alloys & Supplies

- Designed to work on rougher terrain than other small and medium series carts
- 10" pneumatic wheels (with no flat additive)
- Uses a perma clamp to secure its load
- Continuous handle
- 45" H x 30" W
- 19" x 10" base
- 30 lbs.
- 800 lb load capacity
- Assembly required
- Comparable to Saf-T-Cart™ Model 821-10

Stock on Hand

Part Number

CYC191042A10

239

Welding Screens with Frame

- Eyelets on 4 sides
- Nylon ties to tie to frame
- Frame Height 6ft (1750mm)
- 3 widths available (4', 6', 8')
- 14 mil (0.35mm) PVC film



Opaque Curtain

SP-FC46PNF-EDB 4'L x 6'H

SP-FC66PNF-EDB 6'L x 6'H

Frame Only

SP-F66NF

For 6' x 6'
Curtain

Boxed Cylinder Carts

**Assembly
Required**



Part Number

CYC191041SR8 #

Cont. Handle, 19" x 10" base, 41"H, 8" solid tires

CYC191042SR10 ^

Cont. Handle, 19" x 10" base, 42"H, 10" solid tires

CYC140649SR10 *

Cont. Handle, 14" x 6" base, 49"H, 10" solid tires